

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 March 2001 (08.03.2001)

PCT

(10) International Publication Number  
**WO 01/15884 A2**

(51) International Patent Classification<sup>7</sup>: **B29C 45/27**

DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(21) International Application Number: **PCT/NL00/00591**

(22) International Filing Date: 24 August 2000 (24.08.2000)

(25) Filing Language: **Dutch**

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: **English**

(30) Priority Data:  
1012925 27 August 1999 (27.08.1999) NL

Published:

— Without international search report and to be republished upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(71) Applicant and

(72) Inventor: **VAN BOEKEL, Franciscus, Antonius, Jozef**  
[NL/NL]; Voorstraat 119, NL-3311 EN Dordrecht (NL).

(74) Agent: **TABELING, Marcella, Maria, Josefa; Arnold & Siedsma**. Sweelinckplein 1, NL-2517 GK The Hague (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,



**WO 01/15884 A2**

(54) Title: INJECTION-MOULDING DEVICE

(57) Abstract: The invention relates to an injection-moulding device for injection moulding of plastic objects, comprising a mould which defines a mould cavity, in which mould is provided a flow channel for the at least partially liquid plastic, which flow channel extends through a manifold and a number of nozzles connected to the manifold, wherein the flow channel contains a number of transverse separating surfaces between structural components, and at least one transverse separating surface is bridged by a sealing element in the flow channel, which sealing element is provided clampingly on the structural components.

## INJECTION-MOULDING DEVICE

ABSTRACT OF THE DISCLOSURE

The invention relates to an injection-moulding device for injection moulding of plastic objects, having a mould which defines a mould cavity, in which mould is provided a flow channel for the at least partially liquid plastic, which flow channel extends through a manifold and a number of nozzles connected to the manifold, wherein the flow channel contains a number of transverse separating surfaces between structural components, and at least one transverse separating surface is bridged by a sealing element in the flow channel, which sealing element is provided clampingly on the structural components.